

Sanford NA
 2707 Butterfield Road
 Oak Brook, IL 60523
 Phone: 630-481-2000 or 800-323-0749

Emergency Medical Number: 888-786-0972

Creation Date: August 1, 2005

Section One: Product Information

Product Name: Liquid Paper Correction Fluid - Smooth Coverage

Colors: Common White

Includes: Liquid Paper Multi Fluid Correction Fluid, (LPCF-19-13), Liquid Paper 2 in 1

Section Two: Composition

Titanium dioxide (13563-67-7), solvent naphtha (64742-89-8), mineral spirits (64742-48-9), resins, dispersant, colorants, fragrance

Section Three: Hazards Identification

If vapors are deliberately inhaled, the following symptoms may occur: respiratory irritation, dizziness, drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma, and death.

Section Four: First Aid Measures

Inhalation: This product is considered safe under normal use conditions.

Skin Contact: Wash with soap and water.

Eye Contact: Irritation may occur. Wash through with water.

Ingestion: Contact a physician. NOTE TO PHYSICIAN: Contains solvent naphtha and mineral spirits, which may cause chemical pneumonitis.

Section Five: Fire Fighting Measures

Flash Point: 27F (Closed Cup)

Flammability Limits (% by volume): Lower: 1% Upper: 8%

Extinguishing Media: Dry chemical, foam, carbon dioxide.

Special Fire Fighting Measures: In fires involving large quantities, use self-contained breathing apparatus. Cool fire-exposed containers with water spray/fog.

Unusual Fire and Explosion Hazards: Product is flammable. May produce hazardous decomposition products.

Section Six: Accidental Release Measures

In Case of Spill or Accidental Release: Wipe up with absorbent material.

Section Seven: Handling and Storage

Handling: No special handling requirements.

Storage: In large quantities, store in a well-ventilated area.

Section Eight: Exposure Controls and Personal Protection

Eye Protection: None under normal use conditions.
 Clothing: None under normal use conditions.
 Respirator: None under normal use conditions.
 Ventilation: None under normal use conditions.

Section Nine: Physical and Chemical Properties

For product unless otherwise specified:
 Boiling Point: 209 - 230F
 Specific Gravity: ~1.2
 Vapor Pressure: 124 mm Hg at 100F
 Solubility in Water: Negligible
 Evaporation Rate: 3.6 (butyl acetate = 1)
 Appearance; Odor: White fluid; solvent odor

Section Ten: Stability and Reactivity

Stability: Stable
 Conditions to Avoid: Open flames or other ignition sources.
 Chemical Incompatibility: Strong oxidizers
 Hazardous Decomposition: May produce oxides of carbon, nitrogen, and various hydrocarbons in fire.
 Hazardous Polymerization: Will not occur

Section Eleven: Toxicological Information

IARC Monographs: No
 National Toxicology Program: No
 OSHA Regulated: No

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen: Transport Information

ORM-D Consumer Commodity
 Flammable Liquid, n.o.s., (petroleum distillates), Class 3, UN1993, PGI (25.5F CC), Ltd. Qty, EmS#3-07
 Consumer Commodity, 9, ID8000, packing instruction 910

Section Fifteen: Regulatory Information

TSCA INVENTORY: The product on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory

Section Sixteen: Other Information

HMIS Code	
Health	2
Flammability	3
Reactivity	0
Personal Protection	N/A

0=Minimal / 4 = Severe

Sanford NA has been advised by Counsel that the OSHA Hazard Communication Standard does not apply to the Sanford Product described in this Material Safety Data Sheet. The reason for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2004 per the Code of Federal Regulations. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by the Hazard Communication Standard nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard.