

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

SECTION 1- PRODUCT AND MANUFACTURER'S INFORMATION						
NFFPA Rating: Health-1 ; Flammability-2; Reactivity-0 ; Special-A			HMIS Rating: Health-1 Flammability-2 Reactivity-0 Personal Protection-A			
MANUFACTURED FOR: MISSION LABORATORIES 2433 Birkdale Street Los Angeles, CA 90031			DOT Hazard Classification: ORM-D CONSUMER COMMODITY Identity (trade name as used on label): BRITONE FURNITURE POLISH			
Date Prepared: 07/19/07		Prepared By: DS		MSDS Number: 5030 Revision-		
Information Calls: (323) 223-1405			NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA			
EMERGENCY NUMBER: (800) 535-5053						
SECTION 2- HAZARDOUS MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
LIQUIFIED GAS MIXTURE		68476-85-7	N/E	N/E	N/E	N/E
SILICONE EMULSION		N/E	N/E	N/E	N/E	N/E
SECTION 3- PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A			Specific Gravity: < 1.00			
Vapor Pressure: 117 @ 130°F Max.			pH of Product: N/A			
Vapor Density : > 1.00			Evaporation Rate: < 1.00			
Solubility in Water: > 10%			V.O.C. : < 100 gr/L or 10% by weight			
Appearance and Odor: LEMON ODOR, CONE SPRAY						
SECTION 4- FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST FLAMMABLE		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume: Lower: 1.9 - Upper: 9.2		
FLASH POINT AND METHOD USED: N/E			EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.			
SPECIAL FIRE FIGHTING PROCEDURES: Containers should be cooled with water to prevent vapor pressure build up.						
Unusual Fire & Explosion Hazards: At elevated temperatures (over 54°C-130°F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.						
SECTION 5- REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE			HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR			
Incompatibility (Mat. to avoid): VERY STRONG OXIDIZING AGENTS			Conditions to Avoid: Do not store above 54°C-130°F. Keep away from heat, direct sunlight, sparks or open flame. Dropping of containers may cause bursting.			
Hazardous Decomposition Products: Hydrofluoric acid, carbonyl fluoride, oxides of carbon and additional toxic chemicals may be formed in small amounts.						
SECTION 6- HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [X] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS : None Known.						
Inhalation: May cause dizziness and throat irritation.						
Eye or Skin contact: Causes irritation and redness						
Ingestion: (Not considered a potential route of exposure).						
CHRONIC EFFECTS: None Known.						
Medical Conditions Generally Aggravated by Exposure: Preexisting diseases of the Central Nervous System may be aggravated by exposure to this product.						
SECTION 7- EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Remove contact lenses immediately. Flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists.						
Skin Contact: Wash skin with soap and plenty of water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.						
Inhalation: Remove to Fresh Air. Give Oxygen or CPR. Get medical attention.						
Ingestion: Do not give anything by mouth to an unconscious or convulsing person. Do not induce vomiting. Get medical attention.						
SECTION 8- PERSONAL PROTECTION						
Respiratory Protection (specify type): NONE NEEDED WITH GOOD VENTILATION.						
Protective Gloves: (optional) – Chemical resistant gloves.			Eye Protection: SAFETY GLASSES OR MONOGOGGLES.			
Ventilation Requirements: GOOD VENTILATION SHOULD BE MAINTAINED.						
Other Protective Clothing & Equipment: NONE						
Hygienic Work Practices: Ensure strict sanitary conditions are conformed to when working around chemicals.						
SECTION 9- ACCIDENTAL RELEASE PROCEDURES						
Steps To Be Taken If Material Is Spilled Or Released: KEEP UNNECESSARY PEOPLE AWAY. SPILLS ARE SLIPPERY. DIKE & CONTAIN WITH INERT ABSORBENT MATERIAL. COLLECT FOR DISPOSAL.						
Waste Disposal Methods: CONSULT LOCAL AUTHORITY FOR ALTERNATE METHODS. OBSERVE ALL LOCAL, STATE & FEDERAL REGULATIONS.						
Precautions To Be Taken In Handling & Storage: Avoid breathing vapor. Keep away from heat and flame (DO NOT FREEZE). Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 130°F (54°C).						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only